

# A REVIEW OF INVESTIGATIONS ON THE UTILIZATION OF PLASTIC WASTE IN CONCRETE

Henok Abera<sup>1</sup>, Stephen Jebamalai Raj<sup>2</sup>,

<sup>1</sup> Lecturer & Head, Department of Civil Engineering, Kombolcha Institute of Technology, Wollo University, Kombolcha, South Wollo, Ethiopia

<sup>2</sup> Lecturer & Head, Department of Civil Engineering, Kombolcha Institute of Technology, Wollo University, Kombolcha, South Wollo, Ethiopia

## ABSTRACT

Manufacturing activities, service industries, and municipal solid waste all produce significant amounts of waste materials. Waste disposal is further impacting the public's increased concern about the environment. One of the biggest environmental problems in the world is solid waste management. When land filling becomes more expensive and scarcer, the use of waste utilization as an alternative to disposal is attractive. Waste items can be utilized in concrete as part of a research project. While each of these waste products offers a unique effect on the properties of fresh and hardened concrete, discarded tires, plastic, glass, steel, foundry sand, and coal combustion by-products have all had their own effects on the properties of concrete. Waste items are used in concrete, helping to reduce disposal concerns while at the same time making it economical. If it is found that reuse of bulky waste is the best method for dealing with the disposal problem, it will be regarded as the most environmentally responsible solution. A significant type of garbage is plastic, which can be repurposed in a variety of ways. Nevertheless, a number of attempts have been undertaken to investigate its possible application in concrete/asphalt concrete. Our modern lifestyle now depends on plastic, and worldwide plastic production has grown greatly during the previous half century. As a result, a considerable amount of plastic-related garbage is produced. Concrete made using recycled trash and waste plastic has recently gained the interest of researchers, and several studies have been published documenting the behavior of concrete containing recycled waste and waste plastic. Virgin plastic materials were also evaluated to identify similarities and differences between concrete with recycled plastics and concrete with virgin plastic materials. It is crucial for both the construction and plastic recycling industries that new construction materials be developed that use recovered plastics. This article offers a thorough evaluation of the effects of waste and recycled plastics on waste management strategies, as well as information on current research about recycled plastics and their impact on fresh and hardened concrete qualities.

**Keyword:** - *Recycled plastic aggregate concrete, Strength of concrete, Replacement*

## 1. INTRODUCTION

Every year, pollution increases at a higher rate as the population grows. Non-degradable and degradable trash can both be produced. Non-biodegradable garbage takes on a permanent shape over time due to substances which don't decompose, posing an issue with solid waste disposal. Waste management and processing are worldwide problems, especially in densely populated areas. Waste like plastic, demolished concrete, and glass has been embraced as a building material in the most recent scenario. By increasing the quantity of previously-used trash that is incorporated into the concrete, this project has made it easier for the natural materials used in concrete, such as aggregates and sand, to minimize their stress on the natural resources. Cement is the world's second-to-last material used in building, and it is commonly used in practically all civil engineering projects. Incorporating sustainability into modern development is a crucial issue. Reducing waste is critical to numerous environmental issues. Recently, a large number of studies have been dedicated to the use of waste materials in a wide variety of applications. Wasted materials are used for the production of ethanol, starch, acetic acid, and other chemical processes. Organic matter is being removed by using the wastes as adsorbents. Various researchers efficiently carried out the removal of heavy metals and phenol. While various raw and waste materials have been used for bio-ethanol and biodiesel production, numerous efforts have been undertaken and none has been successful. Diesel fuel can be made from waste plastic.

Because of the chemical makeup of plastic and the amount of plastic utilized, plastic waste is a serious challenge faced by developing countries. Road construction materials can be utilized with this plastic to strengthen the road. This could resolve the issue of the disposal of plastics and the creation of new roads. The current summary seeks to synthesize studies on various uses of waste plastic. Plastic extrusion is very important to the solution of this entire problem since it is a technology that turns waste plastic into construction materials that are both sustainable and durable. When this procedure is employed, there is no waste. This does more than just help with construction materials manufacturing. It also aids in dealing with the plastic waste problem. Once plastic is melted and processed continuously, it forms a profile that can be used for a variety of construction applications. No harm is done, and alternative hazardous practices such as landfills, incinerators, and burning are avoided. In general, disposal strategies for plastic in Ethiopia have proven hazardous over time. Landfills, trash incinerators, and littered landfills are some of the methods that are commonly used. Many complications arose as a result of the accidental fire at the waste site. Because of this, the number of cancer patients has increased significantly. Also, infant mortality has become a problem for citizens living close to where cancer patients live. A severe spike in infant mortality has occurred, with the rate rising to 60-80 per thousand live births, compared to the overall city's average of 20-30 per thousand live births. People who litter are doing it. Incinerators also emit hazardous gases when they are burning. Here, it is indisputable that plastic exclusion helps to deal with these issues. Companies that previously were unaware of the negative impact their products had on the environment are starting to focus on their use of recycled plastics such as recyclable rubber, road rail tile resin, and the like. There is also an immediate need to solve these problems, which extrusion is uniquely suited to.

## 2. PLASTIC WASTE MANAGEMENT STRATEGY

Plastic has low biodegradability and so persists in the earth's crust for thousands of years, which causes a disposal problem those results in land and water contamination. Around 10% of all plastic garbage ends up being untreated nowadays. Several studies have been developed to study concrete's features and characteristics by looking at how recyclable debris behaves when it is utilized as an aggregate alternative. This garbage is used to help manage the environment and the environment will benefit from this. While this powdered form of plastic aids the tensile strength of the system, enhanced tensile strength of the system can be obtained by simply providing this ingredient. Conventional cement concrete has a higher compressive strength, but the plastic aggregate contained in concrete diminishes its strength. It is therefore more appropriate to utilize plastic where loads are light, such as roadways, drainage boundaries, etc. Fossil fuels provide over 80% of the raw plastic (oil or natural gas). Most things are made via injection, blow molding, or heat forming the plastic, which is then supplied to manufacturers who then produce the objects using injection, blow molding, or heat forming. These are manufactured and sold directly by brand owners, who use a variety of retail channels to do so. Using this bottle of mineral water as an example, we could say that. When things are used, plastic objects become waste. Because of this, waste management varies significantly from country to country. Developed economies with legislation that encourages recycling are further divided into those that are more developed, and those that are less developed. Meanwhile, developed economies that do not have such incentives are divided into those that are more developed, and those that are less developed.

In developed economies that have waste management policies that encourage recycling, the economy is mature and the infrastructure for trash disposal and energy recovery is good. These economies also have high costs of labor. In Europe and Japan, this applies. The various sorts of recycling regulations have various targets. Organizations are established to oversee recycling more often than you would think. Some of the expenses involved in collecting and sorting plastic debris are financed by these groups. Most funding comes from suppliers, whether they are producers or retailers, or it is earned from customers through environmental fees. This results in allowing various end-of-life management externalities to be reflected in the price of the product. The ability to process and sort plastics on a large scale depends on an infrastructure for plastic sorting and processing that produces recycled plastic that can be used by manufacturers. Some nations have also enacted additional measures, such as levies on landfill and incineration, to increase the cost of traditional processing solutions. Recycling rates in this category range from 30% to 50%. Tight-fisted economies in countries with few or no regulations permit conventional garbage disposal techniques like landfills and incinerators to flourish. typified by the USA and Australia, these countries are

With no requirements to increase its competitiveness, recycling remains underdeveloped and marginal. A much smaller percentage of plastic waste is recycled in the country, with less than 10 percent of it managed locally. Wastewater management systems in industrializing economies are typically below par. Household and industrial garbage still ends up deposited at multiple unofficial and uncontrolled locations, even though collecting everything

and putting it in one place would be ideal. well-developed and coordinated informal networks Recycling is mostly spurred by the market value of waste, and occurs in response to local industrial demands. In these countries, this occurs. Since sorting infrastructure is inadequate, people use informal networks instead.

The infrastructure to process materials expands in accordance with the amount of material available. Recycling rates in this category range from 30% to 50%. As the material has no value in the local market, developing economies with limited industrialisation recycle little of their plastic. Many wastes end up in the ocean, some in rivers and informal dumping, while others are swept out to sea.

### 3. LITERATURE REVIEW

In the examination of waste plastic and waste rubber tires used on flexible roadway pavements, an investigator from the Rokade group found evidence of their use. For the Marshall Method mix design, he produced the semi-dense bituminous concrete (SDBC) mix. Stability, flow, bulk density, and air voids (V<sub>v</sub>, VMA, and VFB) were all discovered in his studies. A higher value of Marshall Stability and greater density were both attained as a result of the bitumen percentage increasing to 5%. The use of plastic trash in road construction was studied by Powel and colleagues. Their research focused on devising a novel technique for plastic disposal as well as quarry dust and tire debris. They also did experiments with specific gravity, grain size analysis, and CBR (certified burn ratio) studies. Plastic waste accumulation results in a decreased maximum dry density, resulting in a lower CBR value. Other things that happened alongside a rise in the quarry dust were an increase in the maximum dry density and CBR value. The study was done by Sarker et. al., who analyzed how waste plastic was converted into valuable chemical compounds. A fraction of a liquid product, which contained around 29% naphtha chemical, was subjected to heat reactions in the course of the examination. plastic debris like HDPE-2, LDPE-4, PP-5, and polystyrene (PS-6). After slurry conversion, thermal liquefaction was performed at 380–430°C and, subsequently, distillation, recovery, and condensation were done. An Nkwachukwu et al. paper highlighted developing countries' sustainable development and plastic recycling. In order to improve facilities and knowledge, most of these plastics end up in unlawful dumping sites or are burned without being collected, according to their study. Their paper examined many environmental issues resulting from the widespread use of plastics. Waste plastic mixed concrete with plasticizer was studied by Rai et al. A number of concrete mixes were made in which various percentages of discarded plastic flakes were used as sand substitutes. Plastic mix concrete was evaluated by comparing results obtained with and without super plasticizer at room temperature. As a result, they determined that reduced workability and compressive strength, which occurred because waste plastic was used as a partial replacement for sand, were small in magnitude and could be increased by the use of superplasticizer. A study conducted by Bhageerathy et. al. has found that biomedical plastic waste can be applied to bituminous road construction. It has been suggested that the amount of plastic in solid waste is rising, and this can only be addressed by recycling it. Another problem that came to light was the state of the roadways. In road construction, they evaluated shredded medical plastic waste in the form of autoclaved needles. The results of the investigation showed that the bituminous mix amended with biomedical plastic waste performed considerably better than previous research had predicted. It was also established that PCC-coated aggregate had specific qualities (PCA). The normal mix turned out to have better qualities for PCA, according to the researchers. In order to find new sources of diesel fuel, Sharma and Soni conducted a study on the generation of alternative diesel fuel from waste oil. Their paper's major goal was to discover non-oil energy options and use them to reduce the damage they caused. In the study, the oils obtained from waste plastic pyrolysis oil, used motor oil, and waste tire oil were examined to find out their qualities. Based on these findings, they estimated that plastic pyrolysis oil, waste motor oil, and waste tire oil produce diesel that is technically feasible, profitable, and a less environmentally harmful option.

Research on the use of plastic waste in flexible pavements was completed by Chavan. Using a shredding machine, she shredded plastic garbage so that it went through a 2-3mm sieve. Heated aggregate and plastic were placed over the aggregate, resulting in a thoroughly coated mix. Plastic-coated asphalt was utilized for road construction alongside bitumen. In addition to strengthening the road structure, adoption of the revolutionary technology will also help boost road life and environmental sustainability. She discovered that by mixing plastic garbage into the mix, it reduces the amount of bitumen needed by roughly 10%. The waste plastic and waste rubber in aggregate and bitumen for road materials research was completed by Wayal and Wagle. As a binding medium for aggregate and bitumen, the team decided to employ polymer and crumbed rubber. They tried testing the material for its ability to withstand crushing, impact, abrasion, and ductility, as well as bitumen penetration, softening point, and ductility.

Easier garbage disposal using waste plastics and rubber tires, ground into a fine powder, is one of the finest options for making flexible pavement.

Other researchers explored the effectiveness of discarded plastic as a flexible pavement building material. Plastic as an innovative technology allowed for more durable roads, and at the same time, added several years to the road's lifespan. Researchers discovered that as the waste plastic load grows in bitumen, the characteristics of aggregate and bitumen improve. Another advantage they discovered was that covering the aggregate with a polymer has numerous benefits. The quality of flexible pavement was improved. Using waste plastic bottles as construction materials was studied by Raut et al. According to them, lowering the construction cost of dwellings might be accomplished by employing waste plastic along with building materials. This claim is also made in reference to bottle houses, which are described as bio-climatic. The phrase bio-climatic suggests that, while it is chilly outside, the inside of the bottle house is also warm.

Although Sahu and Abatneh conducted a preliminary investigation into the conversion of diverse waste plastics into fuel oil, their work has not yet been published. Their work focused on waste plastics that were turned into fuel oil. The research that they were doing centered on thermal cracking of discarded plastic to produce new resources. Due to the effectiveness of the reactor seal, oil production was reduced. The researchers found that for each plastic type, the temperature at which the first drop of oil is obtained is specified. The study was done by Swami et. al., who studied the use of plastic on bituminous roads. They say the widespread use of waste plastic on the road has made the task of disposing of the plastic debris easier because no landfills are required. Also, improved roads were created.

Waste plastics research by Majka and Pielichowski focused on building flood protection systems out of waste plastics. They put out a new proposal in their article for plastic waste management, in which plastic production is increased to provide composite materials that have better flood-protection capabilities. Waste polymer reuse has given numerous new applications and uses for recycling, and the concept was introduced by them.

#### **4. CONCLUSIONS**

1. The problem of plastic waste can be minimized by reuse of plastic.
2. Waste plastic can be used for synthesis of products like ethanol.
3. The use of plastic for road construction is widely investigated area.
4. The strength of the roads constructed with plastic mixed bitumen was found to be more than that constructed with usual material.
5. The conversion of plastic waste into fuel oil was also successfully carried out by few investigators. It can be concluded that use of waste plastic can minimize the disposal problem and add to economical aspects of fuel synthesis and various construction activities.
6. Utilizing the plastic waste as a partial replacement of coarse fine aggregates and cement in concrete may lower down the need of the original ingredients of cement concrete and it also serves as a means to manage these environmental wastes.

Hence, these wastes as a source can be used as a partial replacement of aggregate which ultimately saving the natural resources and hence this study is providing the guidelines for the user to opt these waste materials in concrete production

## 5. REFERENCES

- [1] Sunil J. Kulkarni, Nilesh L. Shinde, Ajaygiri K. Goswami, A Review on Ethanol Production from Agricultural Waste Raw Material, *International Journal of Scientific Research in Science Engineering and Technology*, 2015,1(4),231-233.
- [2] Veena Ramachandran, Nisha Pujari, Tanmay Matey, Sunil Kulkarni, Enzymatic Hydrolysis for Glucose-A Review, *International Journal of Science, Engineering and Technology Research (IJSETR)*, 2013, 2(10), 1937-1942.
- [3] Veena Ramachandran, Nisha Pujari, Tanmay Matey, Sunil Kulkarni, Enzymatic Hydrolysis of Cassava using wheat Seedlings, *International Journal of Science, Engineering and Technology Research (IJSETR)*, 2014,3(5), 1216-1219.
- [4] Kulkarni, Sunil J., and Dr Jayant P. Kaware, Removal of Cadmium from Wastewater by Groundnut Shell Adsorbent-Batch and Column Studies, *International Journal of Chemical Engineering Research*, 2014, 6(1), 27-37.
- [5] Kulkarni Sunil, Kaware Jayant, Adsorption for Phenol Removal- A Review, *International Journal of Scientific Engineering and Research (IJSER)*, 2013, 1(2), 88-96.
- [6] Sunil J. Kulkarni, Removal of phenol from Effluent in Fixed Bed: A Review, *International Journal of Engineering Research and General Science*, 2014, 2(5), 35-38.
- [7] S.J. Kulkarni, Dr. J. P. Kaware ,Isotherm and Kinetics of Phenol Removal by Adsorption-A Review, *International Journal of Research (IJR)*, 2014, 1(8), 287-293.
- [8] D.N. Jadhav, A.K. Vanjara , Removal of Phenol from Wastewater using sawdust, Polymerized sawdust and sawdust Carbon, *Indian Journal of Chemical Technology*, 2004, 1,35-41.
- [9] Sunil J.Kulkarni, Dr. Jayant P. Kaware, Batch Adsorption Process for Phenol Removal using Leaf Litter: Solute Uptake, Kinetic and Isotherm Studies, *International Journal of Environmental Engineering Research*, 2014, 3(2), 23-28.
- [10] Aditya Raut, Mohammad Salman Patel, Nilesh B. Jadhwar, Uzair Khan, Investigating The Application Of Waste Plastic Bottle As A Construction Material- A Review, *Journal Of The International Association Of Advanced Technology And Science*, 2015, 16(16),1-16.
- [11] Yasabie Abatneh, Omprakash Sahu, Preliminary Study On The Conversion Of Different Waste Plastics Into Fuel Oil, *International Journal Of Scientific & Technology Research*, 2013, 2(5),226-229.
- [12] Mrs.Vidula Swami, Abhijeet Jirge, Karan Patil, Suhas Patil, Sushil Patil, Karan Salokhe, Use Of Waste Plastic In Construction Of Bituminous Road, *International Journal Of Engineering Science And Technology*, 2012, 4(5), 2351-2355.
- [13] Tomasz M. Majka, Krzysztof Pielichowski, Application Of Waste Plastics For Efficient Flood Protection Systems, 1st World Sustainability Forum, 1-30 November 2011,1-10.
- [14] Gawande, G. Zamare, V. Renge., S. Tayde and G. Bharsakale, —an overview on waste plastic utilization in asphaltting of roads| *International journal of engineering research and applications.*, *Journal of Engineering Research And Studies*, Vol. 3, Issue 2, April-June 2012, pp 01 -05.
- [15] L.R Schroeder, —The Use of Recycled Materials in Highway construction|, *Public Roads*, Vol 58, Issue 2, 1994.
- [16] An overview of Plastic Waste Management, Central Pollution Control Board, Delhi, 2012, pp. 1-22.
- [17] R. Bharath, A. Varshith, K. Rashmitha, N.G. Ashwath. —Study on Laterite-Cement bricks| Project report, K.V.G College of Engineering, Sullia.DK. 2011 -2012
- [18] P. Sikka, —Plastic Waste Management in India|, Department of science & technology, Government of India, New Delhi, pp. 1-4.
- [19] Lakshmi, R.; Nagan, S. Studies on concrete containing E plastic waste. *Int. J. Environ. Sci.* 2010, 1, 270.
- [20] Senhadji, Y.; Escadeillas, G.; Benosman, A.S.; Mouli, M.; Khelafi, H.; Ould Kaci, S. Effect of incorporating PVC waste as aggregate on the physical, mechanical, and chloride ion penetration behavior of concrete. *J. Adhes. Sci. Technol.* 2015, 29, 625–640.
- [21] Hossain, M.; Bhowmik, P.; Shaad, K. Use of waste plastic aggregation in concrete as a constituent material. *Progress. Agric.* 2016, 27, 383–391.
- [22] Demirboga, R.; Kan, A. Thermal conductivity and shrinkage properties of modified waste polystyrene aggregate concretes. *Constr. Build. Mater.* 2012, 35, 730–734.
- [23] Soroushian, P.; Eldarwish, A.I.; Tlili, A.; Ostowari, K. Experimental investigation of the optimized use of plastic flakes in normal-weight concrete. *Mag. Concr. Res.* 1999, 51, 27–33.

- [24] Farhana, Z.F.; Kamarudin, H.; Rahmat, A.; Al Bakri, A.M. The relationship between water absorption and porosity for geopolymer paste. *Mater. Sci. Forum* 2015, 803, 166–172.
- [25] Krus, M.; Hansen, K.K.; Künzel, H. Porosity and liquid absorption of cement paste. *Mater. Struct.* 1997, 30, 394–398.
- [26] Bertolini, L.; Elsener, B.; Pedferri, P.; Radaelli, E.; Polder, R.B. *Corrosion of Steel in Concrete: Prevention, Diagnosis, Repair*; JohnWiley & Sons: Hoboken, NJ, USA, 2013.
- [27] Broomfield, J.P. *Corrosion of Steel in Concrete: Understanding, Investigation and Repair*; CRC Press: Boca Raton, FL, USA, 2003.
- [28] Fernandes, F.; Manari, S.; Aguayo, M.; Santos, K.; Oey, T.; Wei, Z.; Falzone, G.; Neithalath, N.; Sant, G. On the feasibility of using phase change materials (PCMs) to mitigate thermal cracking in cementitious materials.
- [29] Šavija, B.; Zhang, H.; Schlangen, E. Influence of microencapsulated phase change material (PCM) addition on (micro) mechanical properties of cement paste. *Materials* 2017, 10, 863.
- [30] Liu, D.; Šavija, B.; Smith, G.E.; Flewitt, P.E.J.; Lowe, T.; Schlangen, E. Towards understanding the influence of porosity on mechanical and fracture behaviour of quasi-brittle materials: Experiments and modelling. *Int. J. Fract.* 2017, 205, 57–72.

