

# EXPERIMENTAL STUDY ON STRENGTH OF CONCRETE BY USING METAKAOLIN & OP

Shashikant Dewangan \* Nidhi Gupta \*\*

\*Research Scholar, Department of Civil Engineering, RKDF Institute of Science & Technology, Bhopal

\*\* HOD, Department of Civil Engineering, RKDF Institute of Science & Technology, Bhopal

## ABSTRACT

concrete is that pourable mix of cement, water, sand, and gravel that hardens into a super-strong building material. Supplementary cementing materials (SCM) have become an integral part of concrete mix design. these may be naturally occurring materials, industrial wastes or, by products or the ones requiring less energy to manufacture. some of the commonly used scm are fly ash, silica fume (SF), GGBS, rice husk ash and metakaolin (MK), etc. metakaolin is obtained by the calcination of kaolinite. it is being used very commonly as pozzolanic material and has exhibited considerable influence in enhancing the mechanical and durability properties of concrete. in this paper, experimental study was carried out on M 20 grade and M 50 grade of concrete. in this concrete we have tested slump test, Vee bee test and Compacting Factor of concrete

**Keyword :** Metakaolin, compressive strength, grade of concrete

## INTRODUCTION

Concrete is probably the most extensively used construction material in the world. It is an artificial material in which the aggregates are bonded together by the cement when mixed with water. With the advancement of technology and increased field of application of concrete and mortars, the strength, workability, durability and other characteristics of the ordinary concrete can be made suitable for any situation. For this, definite proportions of cement, water, fine aggregate, coarse aggregate, mineral admixtures and chemical admixtures are required. The demand for Portland cement is increasing dramatically in developing countries. Portland cement production is one of the major reasons for CO<sub>2</sub> emissions into atmosphere. Metakaolin when used as a partial replacement substance for cement in concrete, it reacts with Ca(OH)<sub>2</sub> one of the by-products of hydration reaction of cement and results in additional C-S-H gel which results in increased strength. Metakaolin is obtained by thermal activation of kaolin clay. This activation will cause a substantial loss of water in its constitution causing a rearrangement of its structure. To obtain an adequate thermal activation, the temperature range should be established between 600 to 750°C. The principal reasons for the use of clay-based pozzolans in mortar and concrete have been due to availability of materials and durability enhancement. In addition, it depends on the calcining temperature and clay type. It is also possible to obtain enhancement in strength, particularly during the strength of curing. The very early strength enhancement is due to a combination of the filler effect and acceleration of cement hydration. 1Dinakar et al. investigated the effect of using local calcined kaolin or MK obtained commercially as pozzolan on the development of high strength and permeability/durability characteristics of concrete designed for a very low w/b ratio of 0.3. investigated the effect of partial replacement of cement by metakaolin on the properties of concrete. Supplementary cementing materials (SCMs) have been widely used all over the world in concrete due to their economic and environmental benefits. Hence, they have drawn much attention in recent years. Investigated the porosity and pore size distribution of high performance cement paste blended with metakaolin and compared them with silica fume (SF) or fly ash (FA) blended cement pastes. This present study was concerned with the MK-blended cement pastes at lower w/b ratios. The cement pastes prepared were MK blended pastes with MK contents of 5, 10, and 20%, SF-blended pastes with SF contents of 5 and 10%, an FA blended paste with a FA content of 20%, and a control PC paste without any pozzolanic replacement. The w/b ratio for all the pastes was 0.3.

## MATERIAL

1. Cement
2. Sand

3. Aggregate
4. Metakaolin

## RESULT

Table No 1 M20 and M 50 grade of workability

Sr. No	Type of mix	Slump in mm	Vee- Bee time in sec	Compacting Factor
M 20	OPC Concrete	95	20	0.976
	MK Concrete	65	31	0.930
M 50	OPC Concrete	120	19	0.892
	MK Concrete	105	25	0.862

Fig. No 1 Compressive strength of different mixing proportion

## CONCLUSION

The workability of MKC mixes were workable after adding of super plasticizer at the rate of 1.0% of weight of binding material.

## REFERENCES

- 1) Charles. H., Henage & Doberty. T.J.: "Analysis of reinforced fibrous concrete", Journal of ASCE, Structural Division, Vol-2, No.ST.1, Jan. 1976, PP.177-188.
- 2) Jack synder & David Lankard: "Factors affecting the flexural strength of SFRC", Journal of ACI, Vol.69, No. 2, Feb-1972.
- 3) Kukreja C.B, Kaushik S.K., Kanchi M.B., and Jain O.P., "Flexural characteristics of steel fibre reinforced concrete", Concrete Journal, July (1980), PP.184-188.
- 4) Mohammed Bhai, G.T.G "The residual strength of concrete subjected to elevated temperature". Concrete Journal, Vol 17, No.12, 1983 PP. 22-27.
- 5) Naaman, A.E. and Shah, S.P. "Pull Out Mechanism in Steel- Fibre Reinforced Concrete", Proceedings ASCE, Vol.102, ST.8, August 1976, PP. 1537-1548.
- 6) Narayanan, R., & Kareem-Palanjian., A.S., "Effect of fibre addition on concrete strength", Indian Concrete Journal, April (1984), PP 100-103.
- 7) Narayanan, R., & Kareem-Palanjian., A.S., "Factors Influencing the workability of steel fibre reinforced concrete part-1", Indian Concrete Journal, Oct. (1982), PP. 45-48.
- 8) Rajagopalan. K., Parmasivam & Ramaswamy. G.S.: "Strength of SFRC beams", Indian Concrete Journal, Vol 48, Jan-1974.
- 9) Ramakrishanan, V. et al., "A comparative evaluation of concrete reinforced with straight steel fibres and fibres with deformed ends glued together in to bundles", ACI journal, May-June 1980, PP. 135-143.
- 10) Romualdi. J.P. & Batson. G.B „Mechanics of crack arrest in concrete“ M. Tech., Proceedings of ASCE, Vol-89, EM 3, June 1963, PP. 147-168.
- 11) Sridhara, S. et al., "Fibre reinforced concrete", Indian Concrete Journal, October 1971, PP. 428-442.
- 12) Swamy, R.N., "Fibre reinforced concrete: Mechanics, properties, and applications", Indian Concrete Journal, January 1974, PP. 7-16.