

BATS DETECTION AND REPELLENT SYSTEM

Rohini Bharat Watpade, Deepika Kishor Pagare, Priyanka Narayan Kudhekar, Monika Suryakant Bhingarkar, Prof.S.S.Vaidya

¹ Rohini Bharat Watpade, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India

² Deepika Kishor Pagare, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India

³ Priyanka Narayan Kudhekar, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India

⁴ Monika Suryakant Bhingarkar, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India

⁵ Prof.S.S.Vaidya, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India

ABSTRACT

A sensor is a gadget that changes over one sort of vitality to another. Arduino is a little microcontroller board with a USB fitting to interface with the PC. The Arduino board detects the earth by getting contribution from an assortment of sensors and can eat its environmental factors by controlling LCDs, speakers, engines. Ultrasonic Sensor measure the separation of target objects for example bats or materials through the air utilizing non-contact innovation. They measure separation without harm and are anything but difficult to utilize. The yield Signals got by the sensor are in the simple structure, and yield is carefully arranged and handled by microcontroller. The inward simple to computerized converter is utilized is aligned to get practically exact separation estimation. The deliberate separation is additionally shown on a LCD screen when bats will be distinguished in wanted area lights will turn ON ultrasonic sensor turns on at recurrence 40 hertz for bat aversion.

Keyword: -ATmega328, Servo motor, Ultrasonic Sensor

1.INTRODUCTION

Bats are brilliant animals. Daze from the eyes however the vision is more keen than people, Ultrasonic extending is the procedure utilized by bats. Ultrasonic sensor gives a simple route in separation estimation. The sensor is ideal for separation estimations between moving or stationary articles. Ultrasonic Sensor measure the separation of the articles in air through non-contact system. They measure separation without harm and are anything but difficult to utilize and solid. These separation estimation sensors associate with every normal kind of robotization and telemetry gear. Hardware and procedures in a wide scope of ventures use separation estimation sensors where size or position input is required. Separation estimation sensors are utilized to control or demonstrate the situation of items and materials. Separation estimation sensors can decide the components of articles, for example, tallness, width and measurement, utilizing at least one sensors. The reverberation time reaction of ultrasonic sensor indicator depends on time of movement after trigger heartbeat to the encompassing items is non-direct and relies upon the reflect separation qualities of the article surface. Ultra Sonic sensors are broadly utilized for separation estimation purposes. They over ease and an exactness of under 1 cm in separation estimations of up to 20cm . Be that as it may, the most famous technique utilized in these estimations depends on the hour of flight (ToF) estimation. This ToF is the time slipped by between the emanation and ensuing appearance after impression of a Ultrasonic heartbeat train going at the speed of sound. This causes huge reaction times for a solitary estimation.

1.1 Need for development

In India, nearly 65% of the people are directly or indirectly dependant on agricultural sector for economic survival. The annual income of farmers is significantly influenced by the yield of the crops, which is continuously decreasing due to natural phenomena and poor technological advancement

1.1 Need for development

In India, nearly 65% of the people are directly or indirectly dependant on agricultural sector for economic survival. The annual income of farmers is significantly influenced by the yield of the crops, which is continuously decreasing due to natural phenomena and poor technological advancement..



Fig.1: Prototype1

Be that as it may, the specific consideration ought to be paid to the harm brought about by fowls. As per Maharashtra Rajya Draksha Bagayatdar Sangh (MRDBS), The pinnacle assemblage of grape cultivators, around 4,500 sections of land of the absolute 1.25 lakh section of land reserved for grape development have been influenced by BATs/Indian myna menace. While the specific proportion of the misfortune in grape yield related with winged animals is in corer. ranchers incorporate various customary and ordinary methods to develop and store grains and organic products. A significant number of the pre-owned strategies bring about elimination of the uncommon feathered creatures. Along these lines, there is a need to create elective procedures, for example, exchange with the ranchers, grain stockpiling specialists and specialists in the fields of ornithology, farming areas and field visits, to keep away from irreversible damage to the Indian biodiversity. This examination breaks down the loss of yield of harvest because of fowls, investigates repulsing strategies embraced by the ranchers, and addresses the results of coordinated techniques on the flying creature biodiversity in India.



Fig -2: Prototype2

2. PROPOSED SYSTEM DESIGN

To forestall the issue of crashes with the moving toward trains is tended to right now. The framework depends on a remote sensor labels actualized on untamed life creatures to verify their wellbeing and the human security is utilized. Suitable Wireless collectors are set along the appropriate situations to recognize the action of natural life creatures and to educate their exercises to the concerned individual for verifying the untamed life and human life is sent in framework.

The mishaps caused to wild creatures and especially Elephants are considered. This for the most part happens intracks, when the elephants attempts to cross the track. For that reason elephants in the woods are furnished with exceptional remote beneficiaries which private the nearness of the creature in close nearity. At the point when such an occasion happens the loco pilot is cautioned and the train speed is diminished definitely to stop any mishaps.




Fig -3: Block Diagram Of Prototype

2.1 Component Description

2.1.1 Hardware Requirements

- Arduino ATmega328
- Ultrasonic Sensor
- Servo Motor
- LCD DISPLAY
- GSM Module
- Relay
- Power Supply

2.1.2 Software Requirements

- Arduino IDE
- OrCAD- For block diagram
- Eagle software – for circuit diagram.

3.RESULT




Fig -4: Result of Prototype

4. CONCLUSIONS

We as a whole realize that life Of 70% individuals relies on farm.This homesteads ought to be without assault and innocuous illnesses because of bats pee yet in entire satana district.and at khanpur side,over half of ailments or contaminations are brought about by bats pee .So right now have actualized the framework which will screen the bats assaults during evening time and secures the grape ranches and lychees ranch from bats assaults by repulsing the bats .As the bats is detected,people will get the caution messege that the bats were identified. By utilizing this framework we will ready to forestall the organic products effectively and ranchers won't experienced immense misfortune that they looked from previous2 to multi year.

5. FUTURE SCOPE

We have implemented this project for welfare and for protecting the grape farms and lychees farms. In future, if the government accepts this project idea then it will be practically implemented in many rural areas where the birds attack on fruits or farms. This will be beneficial to reduce the great possibility of infectious diseases and financial loss of farmers which caused due to bats/birds wastes and bats attacks.

In future we can implement this system by using wireless sensors network for flexibility of system

6. ACKNOWLEDGEMENT

We are thankful to HOD of E&TC department, Sanghavi College of Engineering, Nashik for their valuable support also Mr. Sandeep Pachapande Sir for valuable input in paper creation.

7. REFERENCES

- [1] Manabu Ishihara, Makoto Shina, and Shin-nosuke Suzuki, "Evaluation of Method of Measuring Distance Between Object and Walls Using Ultrasonic Sensors", *Journal of Asian Electric Vehicles*, Volume 7, Number 1, June 2009.
- [2] G. Benet, F. Blanes, J.E. Sim, P. Prez, "Using infrared sensors for distance measurement in mobile robots", *Robotics and Autonomous Systems* 40 (2002).
- [3] CA Duberstein, DJ Virden, S Matzner, J Meyer, VI Cullinan AR Maxwell, "Automated Thermal Image Processing for Detection and Classification of Birds and Bats", *Onshore Wind Technology Assessment*, September 2012.
- [4] R. Mark Brigham, Elisabeth K. V. Kalko, Gareth Jones, Stuart Parsons, Herman J. G. A. Limpens, "Bat Echolocation Research: tools, techniques & analysis", Austin, Texas 2002.
- [5] H. O. Lawal, G.O. Adewuyi, A. B. Fawehinmi, A.O. Adeogun, S. O. Etaturvie, "Bioassay of Herbal Mosquito Repellent Formulated from the Essential Oil of Plants", *Journal of Natural Products*, Vol. 5(2012).
- [6] Prof. R. Ugale, "K.K. Wagh College of Agriculture, Saraswati Nagar, Nashik." [9] López-Benítez, M.; Drysdale, T.D.; Hadfield, S.; Maricar, M.I. Prototype for Multidisciplinary Research in the context of the Internet of Things. *J. Netw. Comput. Appl.* 2017, 78, 146–161.
- [10] Xia, Z.; Su, H.; Liu, T. Remote Monitoring System of Lead-Acid Battery Group Based on GPRS. In *Proceedings of the 2010 International Conference on Electrical and Control Engineering (ICECE)*, Wuhan, China, 25–27 June 2010; pp. 4023–4026.
- [11] Rosolem, M.F.N.; Pessenti, G.R.; Beck, R.F.; dos Santos, G.R.; Arioli, V.T.; Lopes, P.H.O. Stationary lead-acid batteries remote monitoring system. In *Proceedings of the 2011 IEEE 33rd International Telecommunications Energy Conference (INTELEC)*, Amsterdam, The Netherlands, 9–13 October 2011.
- [12] Keränen, T.; Karimäki, H.; Viitakangas, J.; Vallet, J.; Ihonen, J.; Hyötylä, P.; Uusalo, H.; Tingelöf, T. Development of integrated fuel cell hybrid power source for electric forklift. *J. Power Sources* 2011, 196, 9058–9068.
- [13] J. Anand, A. Jones, T. K. Sandhya, and K. Besna, "Preserving national animal using wireless sensor network based hotspot algorithm," *IEEE International Conference on Green High Performance Computing (ICGHPC)*, pp. 1-6, 14-15 March 2013.
- [14] E. Cerezuela-Escudero et al., "Performance Evaluation of Neural Networks for Animal Behaviors Classification", *DCAI* 2016.
- [15] M. Dominguez-Morales et al., "Technical viability study for behavioral monitoring of wildlife animals in Doñana", *ICETE* 2011.
- [16] V. Dyo, S.A. Ellwood, D.W. Macdonald, A. Markham, C. Mascolo, B. Pasztor, S. Scellato, N. Trigoni, R. Wohlers, and K. Yousef, "Evolution and sustainability of a wildlife monitoring sensor network," in *Proceedings of the 8th ACM Conference on Embedded Networked Sensor Systems*, pp. 127-140, 2010

BIOGRAPHIES

	<p>Rohini Bharat Watpade Student, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India</p>
	<p>Deepika Kishor Pagare Student, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India</p>
	<p>Priyanka Narayan Kudhekar Student, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India</p>
	<p>Monika Suryakant Bhingarkar Student, Electronics and Telecommunication, SCOE Nashik, Maharashtra, India</p>
	<p>Prof.S.S.Vaidya HOD Electronics and Telecommunication, SCOE Nashik, Maharashtra, India</p>