

EXPERIMENTAL INVESTIGATIONS OF CYLINDER PRESSURE ON A VARIABLE COMPRESSION RATIO DIESEL ENGINE OPERATING WITH DIESEL AND HONGE OIL BLENDS

¹Dr.R.Rajappan, ²G.Gurunathan, ³P.Paramadhayalan, ⁴S.Purushothaman, ⁵R.Girimurugan

¹Professor, ^{2,3,4}Assistant Professor, Department of Mechanical Engineering, Mailam Engineering College, Mailam, Villupuram-604304, Tamilnadu, India.

⁵Assistant Professor, Department of Mechanical Engineering, Nandha College of Technology, Erode-638052, Tamilnadu, India.

ABSTRACT

In this experimental study pressure produced inside the cylinder of a variable compression ratio (VCR) Diesel engine operating with diesel and Honge oil blends were studied under different crank angle (-360° to $+359^{\circ}$), five different loading conditions (0, 3, 6, 9 & 12 kg), two compression ratio (17:01 & 18:01) and three different Honge oil blends (B10, B15 & B20) which are blended with diesel by volume basis (100 ml Honge oil: 900 ml Diesel, 150 ml Honge oil: 850 ml Diesel, 200 ml Honge oil: 800 ml Diesel) respectively. For comparative purpose initially the engine was run by pure Diesel. This study reveals that the cylinder pressure is maximum when the engine operates with pure Diesel on full load conditions at a crank angle of 10° and compression ratio 18. This study reveals that the cylinder pressure is minimum when the engine operates with pure Honge oil blend (B15) on no load conditions at a crank angle of 15° and compression ratio 17.

Keywords: - VCR Diesel engine, cylinder pressure, Honge oil blends, crank angles.

1. INTRODUCTION

The preservation of energy is decreasing now a days and it alleged that it leads to energy demand. In the last two decades, alternative fuels have obtained and identified as essential. A potential biodiesel substitutes diesel oil, consisting of ethyl ester of fatty acids produced by the transesterification reaction of triglycerides of vegetable oils and ethanol with the help of a catalyst. In addition, biodiesel is better than diesel fuel in terms of very low sulfur content and it is also having higher flash and fire point temperatures than in diesel fuel. A lot of research work pointed out that biodiesel has received a significant attention and it is a possible alternative fuel. Biodiesel and its blends with diesel were employed as a fuel for diesel engine without any modifications in the existing engine [1]. The research on the production of biodiesel has increased significantly in recent years because of the need for an alternative fuel which endows with biodegradability, low toxicity and renewability [2]. The biodiesel produced by transesterification showed similar properties to the standard biodiesel [3]. The process of transesterification is found to be an effective method of reducing viscosity of vegetable oil [4]. The lower blends of biodiesel increased the brake thermal efficiency and reduced the fuel consumption. In addition to this, biodiesel blends produce lower engine emissions than diesel [5]. The new fuel Die sterol (combination of diesel fuel, bio ethanol and sunflower methyl ester) as a fuel for diesel engines. The authors revealed that, as the percentage of bio ethanol in the blends is increased, the percentage of CO concentration in the emission is reduced. This trend is due to the fact that bio ethanol has less carbon than diesel [6]. The diesel engine runs with waste plastic oil as fuel. The authors concluded that, the smoke was reduced by 40% than diesel [7]. The new type of biodiesel is prepared from non-edible pongamia pinnata oil by transesterification and used as a fuel in C.I engine. The authors reported that blend B5

exhibits lower engine emissions of unburnt hydrocarbon, carbon monoxide, oxides of nitrogen and carbon dioxide at full load [8]. The experiments were performed in a single cylinder DI diesel engine fueled with a blend of pongamia methyl ester for the proportion of PME10, PME20 and PME30 by volume with diesel fuel for validation of simulated results. The authors observed that there is a good agreement between simulated and experimental results [9]. From the review of literatures, numerous works in the utilization of biodiesel as well as its blends in engines have been done. However, most of the literatures focused on single biodiesel and its blends. From previous studies, it is evident that single biodiesel offers acceptable engine performance and emissions for diesel engine operation.

2. EXPERIMENTAL PLAN

The biodiesel (pongamia pinnata oil and pure diesel) are prepared by the transesterification process. The biodiesel blends were prepared in three different proportions as: Diesel 90%, pongamia pinnata oil 10%; Diesel 85%, pongamia pinnata oil 15%; Diesel 80%, PPEE 10% by volume basis. The various properties like kinematic viscosity, specific gravity, calorific value, flash point temperature and fire point temperature of baseline fuel, raw oils and biodiesel mixed blends were determined by using ASTM methods and compared with diesel properties. The experiments were conducted on a stationary, single cylinder, vertical, four stroke, water cooled, variable compression ratio, diesel engine with electrical loading and the mean gas temperatures were compared with baseline data of diesel fuel.

Table-1 Test engine specifications

Sl.No.	Items	Specifications
1	Type	Vertical, four stroke, single cylinder, VCR engine.
2	Made	Kirloskar oil engines Ltd, Pune, India.
3	Loading device	Eddy current dynamo meter
4	Type of cooling	Water cooled
5	Speed	1500 rpm
6	Power	3.5 kW
7	Bore	87.5mm
8	Compression ratio	12:1 to 20:1
9	Stroke	110mm
10	Fuel	Diesel

Tests were conducted at a constant speed and at varying loads for all biodiesel blends. Engine speed was maintained at 1500 rpm (rated speed) during all experiments. The mean gas temperatures of the exhaust gases were measured by the AVL make smoke meter. The exhaust emissions were measured by the Crypton make five gas analyzer. The experimental set up is shown in Fig. 1 and the detailed engine specifications are also given in Table 1.



Figure 1 Experimental setup

3. RESULTS AND DISCUSSIONS

The following results were drawn from this experimental study which was carried out to investigate the cylinder pressure on a Variable Compression Ratio (VCR) Diesel engine operating with Diesel and three Honge oil blends (B10, B15 & B20) under different crank angle (-360° to +359°), five different loading conditions (0, 3, 6, 9 & 12 kg) and two compression ratio (17:01 & 18:01) respectively.




Figure 2 Effect of cylinder pressure of the VCR engine operating with diesel and compression ratio 17:01




Figure 3 Effect of cylinder pressure of the VCR engine operating with diesel and compression ratio 18:01

3.1 Effect of engine cylinder pressure operating by pure diesel at a compression ratio of 17:01 under various loading conditions

Effect of cylinder pressure of the engine operating by diesel and compression ratio 17:01 for various crank angles were shown in figure.2. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 35.66 and 54.04 bar at 14° & 13° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 17:01.




Figure 4 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B10) and compression ratio 17:01




Figure 5 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B10) and compression ratio 18:01

3.2 Effect of engine cylinder pressure operating by pure diesel at a compression ratio of 18:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Diesel and compression ratio 18:01 for various crank angles were shown in figure.3. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 43.84 and 61.97 bar at 12° & 10° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 18:01.




Figure 6 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B15) and compression ratio 17:01




Figure 7 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B15) and compression ratio 18:01

3.3 Effect of engine cylinder pressure operating by Honge oil (B10) blended with Diesel at a compression ratio of 17:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B10) blended with Diesel and compression ratio 17:01 for various crank angles were shown in figure.4. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 36.31 and 56.27 bar at 13° & 11° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 18:01.




Figure 8 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B20) and compression ratio 17:01




Figure 9 Effect of cylinder pressure of the VCR engine operating with Honge oil blend (B20) and compression ratio 18:01

3.4 Effect of engine cylinder pressure operating by Honge oil (B10) blended with Diesel at a compression ratio of 18:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B10) blended with Diesel and compression ratio 18:01 for various crank angles were shown in figure.5. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 45.46 and 61.84 bar at 11° & 10° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 18:01.

3.5 Effect of engine cylinder pressure operating by Honge oil (B15) blended with Diesel at a compression ratio of 17:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B15) blended with Diesel and compression ratio 18:01 for various crank angles were shown in figure.6. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 35.41 and 54.95bar at 15° & 12° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 17:01.

3.6 Effect of engine cylinder pressure operating by Honge oil (B15) blended with Diesel at a compression ratio of 18:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B15) blended with Diesel and compression ratio 18:01 for various crank angles were shown in figure.7. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 45.32 and 61.82bar at 10° & 11° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 18:01.

3.7 Effect of engine cylinder pressure operating by Honge oil (B20) blended with Diesel at a compression ratio of 17:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B20) blended with Diesel and compression ratio 17:01 for various crank angles were shown in figure.8. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 35.71 and 54.84bar at 15° & 12° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 17:01.

3.8 Effect of engine cylinder pressure operating by Honge oil (B20) blended with Diesel at a compression ratio of 18:01 under various loading conditions

Effect of cylinder pressure of the engine operating by Honge oil (B20) blended with Diesel and compression ratio 18:01 for various crank angles were shown in figure.9. It shows that the cylinder pressure is maximum at the crank angle is zero. The minimum and maximum cylinder pressure obtained in this case is 45.56 and 61.32bar at 10° crank angle respectively. At full load condition and no load conditions the engine cylinder exhibits a maximum and minimum cylinder pressure at a compression ratio of 18:01.

4. SUMMARY

The following conclusions were made from this experimental study which was carried out on a Variable Compression Ratio (VCR) Diesel engine operating with Diesel and three Honge oil blends (B10, B15 & B20) under different crank angle (-360° to +359°), five different loading conditions (0, 3, 6, 9 & 12 kg) and two compression ratio (17:01 & 18:01) respectively.

- In all cases cylinder pressure is maximum at full load condition and minimum at no load conditions.
- At a crank angle of 10° the engine exhibits a better cylinder pressure compared than other crank angles.
- In all cases the engine cylinder pressure is maximum when the engine operates at a compression ratio of 18:01.




Figure 10 Maximum cylinder pressure for different crank angle

- In all cases the engine cylinder pressure is maximum at particular crank angles (10° to 17°).
- The engine cylinder pressure is gradually increases with the increasing Honge oil blends.
- The maximum cylinder pressure obtained from this experimental study is 61.97 bar when the engine operates with pure Diesel on full load conditions at a crank angle of 10° and compression ratio 18.
- The minimum cylinder pressure obtained from this experimental study is 35.41 bar when the engine operates with pure Honge oil blend (B15) on no load conditions at a crank angle of 15° and compression ratio 17.

6. REFERENCES

- [1]. K. Srithar, K. Arun Balasubramanian, V. Pavendan and B. Ashok Kumar, 'Experimental investigations on mixing of two biodiesels blended with diesel as alternative fuel for diesel engines'. Journal of King Saud University – Engineering Sciences, 2014.
- [2]. A.E Ghaly, D. Dave and M. Brooks, 'Production of biodiesel by enzymatic transesterification: review. American journal of biochemical and biotechnology, 2010, Vol.6, pp.54–76.
- [3]. W. Theansuwan, and K. Triratanasirichai, 'The biodiesel production from roast Thai sausage oil by transesterification reaction'. American journal of engineering applications and science, 2011, Vol.4, pp.130–132.
- [4]. D. Agarwal, L. Kumar and A.K. Agarwal, 'Performance evaluation of a vegetable oil fuelled compression ignition engine'. Renewable Energy, 2008, Vol. 33, pp.1147–1156.

- [5]. B. Deepanraj, C. Dhanesh and R. Senthil, 'Use of palm oil biodiesel blends as a fuel for compression ignition engine'. American journal of applied science, Vol.8, pp.1154–1158.
- [6]. H. Rahimi, B. Ghobadian and T. Yusuf, 'Die sterol: an environment-friendly IC engine fuel'. Renewable Energy, 2009, Vol. 34, pp.335–342.
- [7]. M. Mani, C. Subash and G. Nagarajan, 'Performance, emission and combustion characteristics of a DI diesel engine using waste plastic oil'. Application of thermal engineering, 2009, Vol.29, pp.2738–2744.
- [8]. K. Muralidharan, and P. Govindarajan, 'The effect of bio-fuel blends and fuel injection pressure on diesel engine emission for sustainable environment'. 2011, American journal of environmental science, Vol.7, pp.377–382.
- [9]. M.Venkatraman, and G. Devaradjane, 'Computer modeling of a CI engine for optimization of operating parameters such as compression ratio, injection timing and injection pressure for better performance and emission using diesel-diesel biodiesel blends'. American journal of applied science, 2011, Vol.8, pp.897–902.

